

Cover SZER

Ref. B17081M, B17081T, B17083M, B17084M, 17085



APPLICATION

- LED protection and light diffusion in lighting fixtures

MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING




TECHNICAL SPECIFICATIONS

Shape	flat	Finish	Material	Light transmission	Length	Possibility of obtaining a line of light	Ref					
Width	67 mm											
UV resistance	yes											
					frosted			PC	73 %	1000 mm	yes	B17081M_1
										2005 mm		B17081M_2
										3010 mm		B17081M_3
					clear			PC	94 %	1000 mm	no	B17081T_1
										2005 mm		B17081T_2
										3010 mm		B17081T_3
					frosted			PC	63 %	1000 mm	yes	B17083M_1
										2005 mm		B17083M_2
										3010 mm		B17083M_3
					frosted			PMMA	88 %	1000 mm	no	B17084M_1
										2005 mm		B17084M_2
		3010 mm	B17084M_3									
		frosted	PMMA	88 %	1000 mm	no	17085_1					
					2005 mm		17085_2					
					3010 mm		17085_3					

Cover SZER

Ref. B17081M, B17081T, B17083M, B17084M, 17085

RELATED PROFILES > FOR MAIN LIGHTING



SEPOD
A06593